



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		1/96
Last revised date :	11.04.2022		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Ammonia, anhydrous

Trade name: Ammonia 3.0, Ammonia 3.6 Detector, Ammonia 3.8, Ammonia 4.5, Ammonia 5.0, Ammonia 6.0, R717

Additional identification

Chemical name: Ammonia, anhydrous

Chemical formula: NH₃

INDEX No. 007-001-00-5

CAS-No. 7664-41-7

EC No. 231-635-3

REACH Registration No. 01-2119488876-14

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional use for chemical analysis, calibration, (routine) quality control, laboratory use. Under controlled conditions. Industrial and professional. Perform risk assessment prior to use. Casting operations Use in explosives Freezing, chilling, and packaging of foodstuffs. Manufacturing of fertilisers and nitric acid. Production of plastics. Refrigerant. Use for electronic component manufacture. Use of gas to manufacture pharmaceutical products. Using gas alone or in mixtures for the calibration of analysis equipment. Using gas as feedstock in chemical processes. Using gas for metal treatment. Washing of textiles or metal parts Water treatment. Use in laboratories Formulation of mixtures with gas in pressure receptacles.

Uses advised against Contact supplier for more information on uses. Uses other than those listed above are not supported.Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier
 Linde Gas AB
 Rättarvägen 3
 169 68 Solna

Telephone: +46 8 7069500



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		2/96
Last revised date :	11.04.2022		

E-mail: sds.ren@linde.com

1.4 Emergency telephone number: Poison center: 020-99 60 00 (24 h). Emergency number: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas	Category 2	H221: Flammable gas.
Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.

Health Hazards

Acute toxicity (Inhalation - gas)	Category 3	H331: Toxic if inhaled.
Skin corrosion	Category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage	Category 1	H318: Causes serious eye damage.

Environmental Hazards

Acute hazards to the aquatic environment	Category 1	H400: Very toxic to aquatic life.
Chronic hazards to the aquatic environment	Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label Elements

Contains: Ammonia, anhydrous



Signal Word: Danger



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		3/96
Last revised date :	11.04.2022		

Hazard Statement(s): H221: Flammable gas.
 H280: Contains gas under pressure; may explode if heated.
 H331: Toxic if inhaled.
 H314: Causes severe skin burns and eye damage.
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements

General None.

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260: Do not breathe gas/vapors.
 P273: Avoid release to the environment.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response: P303+P361+P353+P315: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Get immediate medical advice/attention.
 P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.
 P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
 P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 P381: In case of leakage, eliminate all ignition sources.

Storage: P403: Store in a well-ventilated place.
 P405: Store locked up.

Disposal None.

Supplemental information

EUH071: Corrosive to the respiratory tract.

Unknown toxicity - Health

Acute toxicity, inhalation, gas 0 %



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		4/96
Last revised date :	11.04.2022		

Unknown toxicity - Environment

Acute hazards to the aquatic environment	0 %
Chronic hazards to the aquatic environment	0 %

2.3 Other hazards

Contact with evaporating liquid may cause frostbite or freezing of skin.
Not classified as PBT or vPvB.

Endocrine disrupting properties-Toxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties-Ecotoxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		5/96
Last revised date :	11.04.2022		

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name Ammonia, anhydrous
INDEX No.: 007-001-00-5
CAS-No.: 7664-41-7
EC No.: 231-635-3
REACH Registration No.: 01-2119488876-14
Purity: 100%
 The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name: Ammonia 3.0, Ammonia 3.6 Detector, Ammonia 3.8, Ammonia 4.5, Ammonia 5.0, Ammonia 6.0, R717

Chemical name	Chemical formula	Concentration	CAS-No.	EC No.	REACH Registration No.	M-Factor:	Notes
Ammonia, anhydrous	NH3	100%	7664-41-7	231-635-3	01-2119488876-14	Aquatic Toxicity (Acute): 1	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

This substance is listed as SVHC.PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

SECTION 4: First aid measures

General: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		6/96
Last revised date :	11.04.2022		

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Treat with a corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam.

Unsuitable extinguishing media: Carbon Dioxide. Do not use water jet, as this may cause corrosive liquid to splash.

5.2 Special hazards arising from the substance or mixture: Fire or excessive heat may produce hazardous decomposition products.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		7/96
Last revised date :	11.04.2022		

Hazardous Combustion Products: If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Nitrogen monoxide ; Nitrogen dioxide

5.3 Advice for firefighters

Special fire-fighting procedures:

In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters:

Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus.
Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres . In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation. Eliminate sources of ignition. Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4 Reference to other sections:

Refer to sections 8 and 13.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		8/96
Last revised date :	11.04.2022		

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		9/96
Last revised date :	11.04.2022		

should be in place.

7.2 Conditions for safe storage, including any incompatibilities:

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Keep away from food, drink and animal feeding stuffs. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s): None.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Form of exposure	Exposure Limit Values	Source
ammonia, anhydrous	TWA		20 ppm 14 mg/m ³	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
	STEL		50 ppm 36 mg/m ³	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
	NGV		20 ppm 14 mg/m ³	Sweden. Occupational Exposure Limit Values, as amended (2018)
	TGV		50 ppm 36 mg/m ³	Sweden. Occupational Exposure Limit Values, as amended (2018)

Please refer to the latest edition of the appropriate source text and consult an industrial hygienist or similar professional, or local agencies, for further information.

Biological Limit Values

No biological exposure limits noted for the ingredient(s).



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		10/96
Last revised date :	11.04.2022		

DNEL-Values

Critical component	Type	Value	Remarks
Ammonia, anhydrous	Workers - Inhalation, Systemic, short-term	47,6 mg/m ³	Repeated dose toxicity
	Workers - Inhalation, Systemic, long-term	47,6 mg/m ³	Repeated dose toxicity
	Workers - Inhalation, Local, short-term	36 mg/m ³	respiratory tract irritation
	Workers - Inhalation, Local, long-term	14 mg/m ³	respiratory tract irritation
	Workers - Dermal, Systemic, long-term	6,8 mg/kg bw/day	Repeated dose toxicity
	Workers - Eyes, Local effect		Medium hazard (no threshold derived)
	Workers - Dermal, Systemic, short-term	6,8 mg/kg bw/day	Repeated dose toxicity
	Workers - Dermal, Local, long-term, Local, short-term		Medium hazard (no threshold derived), Skin irritation/corrosion

PNEC-Values

Critical component	Type	Value	Remarks
Ammonia, anhydrous	Aquatic (intermit. releases)	8 µg/l	-
Ammonia, anhydrous	Aquatic (marine water)	1,1 µg/l	-
Ammonia, anhydrous	Aquatic (freshwater)	1,1 µg/l	-

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Gas detectors should be used when quantities of flammable gases or vapours may be released. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges. Do not eat, drink or smoke when using the product.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		11/96
Last revised date :	11.04.2022		

Individual protection measures, such as personal protective equipment

General information: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

Eye/face protection: Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection:

Guideline: EN 388 Protective gloves against mechanical risks.
 Additional Information: Wear working gloves while handling containers
 Material: Chloroprene rubber.
 Break-through time: 30 min
 Glove thickness: 0,5 mm
 Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms.
 Additional Information: Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
 Material: Butyl rubber.
 Break-through time: 480 min
 Glove thickness: 0,7 mm
 Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms.
 Additional Information: Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		12/96
Last revised date :	11.04.2022		

Body protection: Wear fire resistant or flame retardant clothing. Keep suitable chemically resistant protective clothing readily available for emergency use.
 Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing. Guideline: EN 943 Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.

Other: Wear safety shoes while handling containers
 Guideline: ISO 20345 Personal protective equipment - Safety footwear.

Respiratory Protection: Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres
 Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking. Material: Filter K
 Guideline: EN 14387 Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking.
 Guideline: EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking.

Thermal hazards: No precautionary measures are necessary.

Hygiene measures: Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.

Environmental exposure controls: For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
Appearance



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		13/96
Last revised date :	11.04.2022		

Physical state:	Gas
Form:	Liquefied gas
Color:	Colorless
Odor:	Pungent suffocating odor
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.
Melting Point:	-107,9 °F/-77,7 °C Experimental result, Key study
Boiling Point:	-27 °F/-33 °C
Flammability:	Flammable Gas
Upper/lower limit on flammability or explosive limits	
Explosive limit - upper:	25 %(V) Experimental result, Key study
Explosive limit - lower:	16 %(V)
Flash Point:	Not applicable to gases and gas mixtures.
Autoignition Temperature:	651 °C Experimental result, Key study
Decomposition Temperature:	> 842 °F/> 450 °C
pH:	If dissolved in water pH-value will be affected.
Viscosity	
Dynamic viscosity:	0,255 mPa.s (-28,3 °F/-33,5 °C) Experimental result, Key study
Kinematic viscosity:	No data available.
Solubility(ies)	
Solubility in Water:	531 g/l (68 °F/20 °C)
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	0,23 Other, Weight of Evidence study 2 = reliable with restrictions
Dispersion Stability:	No data available.
Vapor pressure:	8,5737 bar (68 °F/20 °C) Experimental result, Key study
Relative density:	0,68 (-27 °F/-33 °C)
Density:	0,61 g/cm ³ (68,0 °F/20,0 °C) 0,563 g/cm ³ (122,0 °F/50,0 °C)
Relative vapor density:	0,59 AIR=1 77 °F/25 °C
Particle characteristics:	Not applicable



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		14/96
Last revised date :	11.04.2022		

9.2 Other information

Flammability:	Tci: 40,1
Molecular weight:	17,03 g/mol (NH ₃)
Critical Temp. (°C):	132,0 °C

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	Can form a potentially explosive atmosphere in air. May react violently with oxidants.
10.4 Conditions to avoid:	Avoid moisture in the installation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible Materials:	Air and oxidizers. Moisture. For material compatibility see latest version of ISO-11114. Reacts with water to form corrosive alkalis. May react violently with acids.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

General information: Inhalation of large amounts leads to bronchospasm, laryngeal oedema and pseudomembrane formation.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Oral Product Based on available data, the classification criteria are not met.

Ammonia, anhydrous LD 50 (Rat): 350 mg/kg Remarks: Experimental result, Key study



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		15/96
Last revised date :	11.04.2022		

**Acute toxicity - Dermal
Product**

Based on available data, the classification criteria are not met.

**Acute toxicity - Inhalation
Product**

Toxic if inhaled.

Ammonia, anhydrous

LC 50 (Rat, 4 h): 2000 ppm

Repeated dose toxicity

Ammonia, anhydrous

NOAEL (Rat(Female, Male), Oral, 28 - 53 d): 250 mg/kg Gavage Experimental result, Key study
 LOAEL (Rat, Inhalation, 35 d): 175 mg/m3 Experimental result, Weight of Evidence study
 LOAEL (Rat(Female, Male), Oral, 28 - 53 d): 750 mg/kg Gavage Experimental result, Key study
 NOAEL (Wistar rat(Male), Inhalation, 50 d): 35 mg/m3 Experimental result, Weight of Evidence study

**Skin Corrosion/Irritation
Product**

Causes severe burns.

**Serious Eye Damage/Eye Irritation
Product**

Causes serious eye damage.

**Respiratory or Skin Sensitization
Product**

Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity
Product**

Based on available data, the classification criteria are not met.

In vitro

Ammonia, anhydrous

Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)): Negative.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		16/96
Last revised date :	11.04.2022		

In vivo

Ammonia, anhydrous Micronucleus test in vivo mouse: (OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)) (Mouse, Male): Negative.

Carcinogenicity

Product Based on available data, the classification criteria are not met.

Ammonia, anhydrous Rat (, Male); Oral (OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies))
 NOAEL (Maternal toxicity): 256 mg/kg bw/day
 Rat (, Female); Oral (OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies))
 NOAEL (Maternal toxicity): 284 mg/kg bw/day

Reproductive toxicity

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product Based on available data, the classification criteria are not met.

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

11.2 Information on other hazards

Endocrine disrupting properties

Product: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.;

Components:

Ammonia, anhydrous The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.;



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		17/96
Last revised date :	11.04.2022		

Other information

Product: No data available.

SECTION 12: Ecological information

General information: Avoid release to the environment. Product is not allowed to be discharged into ground water or the aquatic environment. Not applicable

12.1 Toxicity

Acute toxicity

Product Very toxic to aquatic life with long lasting effects.

Acute toxicity - Fish

Ammonia, anhydrous LC 50 (Pimephales promelas, 96 h): 0,75 - 3,4 mg/l (flow-through) Remarks: 2 = reliable with restrictions Experimental result, Key study

Acute toxicity - Aquatic Invertebrates

Ammonia, anhydrous LC 50 (48 h): 101 mg/l Remarks: Experimental result, Key study

Toxicity to microorganisms

Ammonia, anhydrous NOEC (72 h): >= 15 mg/l (OECD Guideline 201 (Freshwater Alga and Cyanobacteria, Growth Inhibition Test))
Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible.

Toxicity to terrestrial organisms

Ammonia, anhydrous Study not necessary due to exposure considerations.

Chronic Toxicity - Fish

Ammonia, anhydrous NOEC (Lepomis cyanellus, 40 d): 0,22 µg/l (flow-through)



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		18/96
Last revised date :	11.04.2022		

Chronic Toxicity - Aquatic Invertebrates

Ammonia, anhydrous NOEC (Daphnia magna, 21 d): 0,79 mg/l (flow-through) 2 = reliable with restrictions Experimental result, Key study

Toxicity to Aquatic Plants

Ammonia, anhydrous LC 50 (Algae, algal mat (Algae), 18 Days): 2.700 mg/l

**12.2 Persistence and Degradability
Product**

Not applicable to gases and gas mixtures..

Biodegradation

Inorganic The product is not readily biodegradable.

**12.3 Bioaccumulative potential
Product**

The substance has no potential for bioaccumulation.

**12.4 Mobility in soil
Product**

The substance has low mobility in soil.

**12.5 Results of PBT and vPvB
assessment
Product**

Not classified as PBT or vPvB.

Other Ecological Information

May cause pH changes in aqueous ecological systems. Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible.

12.6 Endocrine disrupting properties:

Product: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Components:



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		19/96
Last revised date :	11.04.2022		

Ammonia, anhydrous

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects:

Other hazards

Product: No data available.

Other effects:

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Must not be discharged to atmosphere. Consult supplier for specific recommendations.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws. Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere. Gas may be scrubbed in water. Gas may be scrubbed in sulphuric acid solution.

European Waste Codes

Container: 16 05 04*: Gases in pressure containers (including halons) containing hazardous substances.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		20/96
Last revised date :	11.04.2022		

SECTION 14: Transport information

ADR

- 14.1 UN number or ID number: UN 1005
- 14.2 UN Proper Shipping Name: AMMONIA, ANHYDROUS
- 14.3 Transport Hazard Class(es)
 - Class: 2
 - Label(s): 2.3, 8
 - Hazard No. (ADR): 268
 - Tunnel restriction code: (C/D)
- 14.4 Packing Group: -
 - Limited quantity: None.
 - Excepted quantity: E0
- 14.5 Environmental hazards: Environmentally Hazardous
- 14.6 Special precautions for user: -

ADN

- 14.1 UN number or ID number: UN 1005
- 14.2 UN Proper Shipping Name: AMMONIA, ANHYDROUS
- 14.3 Transport Hazard Class(es)
 - Class: 2
 - Label(s): 2.3, 8
 - Hazard No. (ADR): -
- 14.4 Packing Group: -
 - Limited quantity: None.
 - Excepted quantity: E0
- 14.5 Special precautions for user: None.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		21/96
Last revised date :	11.04.2022		

RID

- 14.1 UN number or ID number: UN 1005
- 14.2 UN Proper Shipping Name AMMONIA, ANHYDROUS
- 14.3 Transport Hazard Class(es)
 - Class: 2
 - Label(s): 2.3, 8
- 14.4 Packing Group: -
 - Limited quantity None.
 - Excepted quantity E0
- 14.5 Environmental hazards: Environmentally Hazardous
- 14.6 Special precautions for user: -

IMDG

- 14.1 UN number or ID number: UN 1005
- 14.2 UN Proper Shipping Name: AMMONIA, ANHYDROUS
- 14.3 Transport Hazard Class(es)
 - Class: 2.3
 - Label(s): 2.3, 8
 - EmS No.: F-C, S-U
- 14.4 Packing Group: -
 - Limited quantity None.
 - Excepted quantity E0
- 14.5 Environmental hazards: MARINE POLLUTANT
- 14.6 Special precautions for user: -

IATA

- 14.1 UN number or ID number: UN 1005
- 14.2 Proper Shipping Name: Ammonia, anhydrous
- 14.3 Transport Hazard Class(es):
 - Class: 2.3
 - Label(s): -
- 14.4 Packing Group: -
 - Limited quantity None.
 - Excepted quantity None.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		22/96
Last revised date :	11.04.2022		

14.5 Environmental hazards: Environmentally Hazardous

14.6 Special precautions for user: -

Other information

Passenger and cargo aircraft: Forbidden.

Cargo aircraft only: Forbidden.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

Additional identification:

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. REACH Annex XIV, Substances Subject to Authorization as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended: None present or none present in regulated quantities.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		23/96
Last revised date :	11.04.2022		

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, Annex I:

Chemical	CAS-No.	Lower-tier Requirements	Upper-tier Requirements
Ammonia, anhydrous	7664-41-7	50 t	200 t

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Ammonia, anhydrous	7664-41-7	100%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work
 Directive 2016/425/EEC on personal protective equipment
 Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.
 This Safety Data Sheet has been produced to comply with Regulation (EU) 2020/878.

15.2 Chemical safety assessment: Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.

Abbreviations and acronyms:

ECTLV: EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended
 SWO: Sweden. Occupational Exposure Limit Values, as amended
 ECTLV / STEL: Short Term Exposure Limit (STEL):
 ECTLV / TWA: Time Weighted Average (TWA):
 SWO / TGV: Ceiling Limit Value:

SDS_SE - 000010021772



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		24/96
Last revised date :	11.04.2022		

SWO / NGV: Time Weighted Average (TWA):

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; EIGA - European Industrial Gases Association; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		25/96
Last revised date :	11.04.2022		

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)

(<http://www.atsdr.cdc.gov/>).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances

<http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.

International Programme on Chemical Safety (<http://www.inchem.org/>)

ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network

TOXNET (<http://toxnet.nlm.nih.gov/index.html>)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H221	Flammable gas.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Training information:

Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		26/96
Last revised date :	11.04.2022		

Classification according to Regulation (EC) No 1272/2008 as amended.

- Flam. Gas 2, H221
- Press. Gas Liq. Gas, H280
- Acute Tox. 3, H331
- Skin Corr. 1B, H314
- Eye Dam. 1, H318
- Aquatic Acute 1, H400
- Aquatic Chronic 2, H411

Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date:

05.04.2024

Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		27/96
Last revised date :	11.04.2022		

Annex to the extended Safety Data Sheet (eSDS)

Content

Exposure Scenario 1.	Industrial use, Formulation & (re)packing of substances and mixtures
Exposure Scenario 2.	Industrial use, Manufacture of fine chemicals
Exposure Scenario 3.	Industrial use, Metal surface treatment products
Exposure Scenario 4.	Industrial use, Manufacture of computer, electronic and optical products, electrical equipment
Exposure Scenario 5.	Industrial use, Exhaust gas DeNOx applications
Exposure Scenario 6.	Industrial use, Non-metal-surface treatment products, Treatment of plastics
Exposure Scenario 7.	Industrial use, Non-metal-surface treatment products, Treatment of textiles
Exposure Scenario 8.	Professional use, Laboratory activities
Exposure Scenario 9.	Professional use, Refilling of refrigeration equipment
Exposure Scenario 10.	Professional use, Water treatment chemicals

Exposure Scenario 1.

Exposure scenario worker

1. Industrial use, Formulation & (re)packing of substances and mixtures

List of use descriptors	
Sector(s) of use	
Product categories [PC]:	

Name of contributing environmental scenario and corresponding ERC	Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.: ERC2: Formulation into mixture
---	--

Contributing Scenarios	Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.: PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment
------------------------	--



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		28/96
Last revised date :	11.04.2022		

	<p>conditions</p> <p>PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities</p>
--	--

2.1. Contributing exposure scenario controlling environmental exposure for: Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:

Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used

Daily amount per site	3030 tonnes
Regional use tonnage:	11515 tonnes/day

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		29/96
Last revised date :	11.04.2022		

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		30/96
Last revised date :	11.04.2022		

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		31/96
Last revised date :	11.04.2022		

Remarks	not relevant
---------	--------------

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1, PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor use				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions, Transfer of substance or mixture (charging and discharging) at dedicated facilities

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		32/96
Last revised date :	11.04.2022		

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Handle product within a closed system.				Transfer of substance or mixture (charging and discharging) at dedicated facilities
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		33/96
Last revised date :	11.04.2022		

				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable gloves tested to EN374: 90 %			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable face shield.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable coveralls to prevent exposure to the skin.			Transfer of substance or mixture (charging and discharging) at dedicated facilities



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		34/96
Last revised date :	11.04.2022		

		Use suitable eye protection.		Transfer of substance or mixture (charging and discharging) at dedicated facilities
--	--	------------------------------	--	---

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:

none

Health:

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 2.

Exposure scenario worker

1. Industrial use, Manufacture of fine chemicals

List of use descriptors	
Sector(s) of use	SU9: Manufacture of fine chemicals
Product categories [PC]:	PC21: Laboratory chemicals



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		35/96
Last revised date :	11.04.2022		

Name of contributing environmental scenario and corresponding ERC	<u>Using gas as feedstock in chemical processes.:</u> ERC6a: Use of intermediate
---	---

Contributing Scenarios	<p><u>Using gas as feedstock in chemical processes.:</u></p> <p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p>
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas as feedstock in chemical processes., Precursor for fertiliser/explosive manufacture, Use of gas to manufacture pharmaceutical products.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used

Daily amount per site	2424 tonnes
-----------------------	-------------



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		36/96
Last revised date :	11.04.2022		

Regional use tonnage:	11515 tonnes/day
-----------------------	------------------

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		37/96
Last revised date :	11.04.2022		

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas as feedstock in chemical processes., Precursor for fertiliser/explosive manufacture, Use of gas to manufacture



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		38/96
Last revised date :	11.04.2022		

pharmaceutical products.

Process Categories:	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p>
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1, PROC2, PROC3

Human factors not influenced by risk management

This information is not available.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		39/96
Last revised date :	11.04.2022		

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor use				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions, Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Apply a good standard of general				Chemical production or refinery in closed process



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		40/96
Last revised date :	11.04.2022		

or controlled ventilation when maintenance activities are carried out.				without likelihood of exposure or processes with equivalent containment conditions
Handle product within a closed system.				Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
Handle product within a closed system.				Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally				Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		41/96
Last revised date :	11.04.2022		

required.				
-----------	--	--	--	--

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
	Wear suitable gloves tested to EN374: 90			Chemical production or refinery in closed continuous



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		42/96
Last revised date :	11.04.2022		

	%			process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
	Wear suitable face shield.			Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
	Wear suitable coveralls to prevent exposure to the skin.			Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
		Use suitable eye protection.		Chemical production or refinery in closed continuous



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		43/96
Last revised date :	11.04.2022		

				process with occasional controlled exposure or processes with equivalent containment conditions Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
--	--	--	--	---

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas as feedstock in chemical processes., Precursor for fertiliser/explosive manufacture, Use of gas to manufacture pharmaceutical products.:

none

Health:

Using gas as feedstock in chemical processes., Precursor for fertiliser/explosive manufacture, Use of gas to manufacture pharmaceutical products.:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 3.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		44/96
Last revised date :	11.04.2022		

Exposure scenario worker

1. Industrial use, Metal surface treatment products

List of use descriptors

Sector(s) of use	SU14: Manufacture of basic metals, including alloys SU15: Manufacture of fabricated metal products, except machinery and equipment
Product categories [PC]:	PC14: Metal surface treatment products

Name of contributing environmental scenario and corresponding ERC	<u>Using gas for metal treatment.:</u> ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)
---	--

Contributing Scenarios	<u>Using gas for metal treatment.:</u> PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature
------------------------	--

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas for metal treatment., Aluminium casting

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		45/96
Last revised date :	11.04.2022		

Daily amount per site	76 tonnes
Regional use tonnage:	1073 tonnes/day

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		46/96
Last revised date :	11.04.2022		

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		47/96
Last revised date :	11.04.2022		

2.2. Contributing exposure scenario controlling worker exposure for: Using gas for metal treatment., Aluminium casting

Process Categories:	PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC22

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor				Manufacturing and processing of minerals



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		48/96
Last revised date :	11.04.2022		

use				and/or metals at substantially elevated temperature
-----	--	--	--	---

Other relevant operational conditions:	. See section 8 of the SDS.
---	-----------------------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Manufacturing and processing of minerals and/or metals at substantially elevated temperature
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Manufacturing and processing of minerals and/or metals at substantially elevated temperature

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		49/96
Last revised date :	11.04.2022		

				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed
--	--	--	--	---

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Manufacturing and processing of minerals and/or metals at substantially elevated temperature
	Wear suitable gloves tested to EN374: 90 %			Manufacturing and processing of minerals and/or metals at substantially elevated temperature
	Wear suitable face shield.			Manufacturing and processing of minerals and/or metals at substantially elevated temperature
	Wear suitable coveralls to prevent exposure to the skin.			Manufacturing and processing of minerals and/or metals at substantially elevated temperature
		Use suitable eye protection.		Manufacturing and processing of minerals



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		50/96
Last revised date :	11.04.2022		

				and/or metals at substantially elevated temperature
--	--	--	--	---

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas for metal treatment., Aluminium casting:

none

Health:

Using gas for metal treatment., Aluminium casting:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 4.

Exposure scenario worker

1. Industrial use, Manufacture of computer, electronic and optical products, electrical equipment

List of use descriptors	
Sector(s) of use	SU16: Manufacture of computer, electronic and optical products, electrical equipment
Product categories [PC]:	PC33: Semiconductors



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		51/96
Last revised date :	11.04.2022		

Name of contributing environmental scenario and corresponding ERC	Use for electronic component manufacture.: ERC6a: Use of intermediate
---	--

Contributing Scenarios	Use for electronic component manufacture.: PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Use for electronic component manufacture.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used

Daily amount per site	2424 tonnes
Regional use tonnage:	11515 tonnes/day

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		52/96
Last revised date :	11.04.2022		

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		53/96
Last revised date :	11.04.2022		

Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Use for electronic component manufacture.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		54/96
Last revised date :	11.04.2022		

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor use				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		55/96
Last revised date :	11.04.2022		

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		56/96
Last revised date :	11.04.2022		

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Use for electronic component manufacture.:

none

Health:

Use for electronic component manufacture.:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 5.

Exposure scenario worker

1. Industrial use, Exhaust gas DeNOx applications

List of use descriptors	
Sector(s) of use	SU23: Electricity, steam, gas water supply and sewage treatment
Product categories [PC]:	PC20: Processing aids such as pH-regulators, flocculants, precipitants,



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		57/96
Last revised date :	11.04.2022		

	neutralization agents
--	-----------------------

Name of contributing environmental scenario and corresponding ERC	Exhaust gas DeNOx applications: ERC6a: Use of intermediate
---	---

Contributing Scenarios	Exhaust gas DeNOx applications: PROC23: Open processing and transfer operations at substantially elevated temperature
------------------------	--

2.1. Contributing exposure scenario controlling environmental exposure for: Exhaust gas DeNOx applications

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used

Daily amount per site	2424 tonnes
Regional use tonnage:	11515 tonnes/day

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		58/96
Last revised date :	11.04.2022		

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		59/96
Last revised date :	11.04.2022		

Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Exhaust gas DeNOx applications

Process Categories:	PROC23: Open processing and transfer operations at substantially elevated temperature
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
-------------------------------	---------------------------



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		60/96
Last revised date :	11.04.2022		

Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC23

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor use				Open processing and transfer operations at substantially elevated temperature

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		61/96
Last revised date :	11.04.2022		

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Open processing and transfer operations at substantially elevated temperature
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Open processing and transfer operations at substantially elevated temperature

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		62/96
Last revised date :	11.04.2022		

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Open processing and transfer operations at substantially elevated temperature
	Wear suitable gloves tested to EN374: 90 %			Open processing and transfer operations at substantially elevated temperature
	Wear suitable face shield.			Open processing and transfer operations at substantially elevated temperature
	Wear suitable coveralls to prevent exposure to the skin.			Open processing and transfer operations at substantially elevated temperature
		Use suitable eye protection.		Open processing and transfer operations at substantially elevated temperature

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Exhaust gas DeNOx applications:

none

Health:



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		63/96
Last revised date :	11.04.2022		

Exhaust gas DeNOx applications:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 6.

Exposure scenario worker

1. Industrial use, Non-metal-surface treatment products, Treatment of plastics

List of use descriptors	
Sector(s) of use	SU12: Manufacture of plastics products, including compounding and conversion
Product categories [PC]:	PC15: Non-metal surface treatment products

Name of contributing environmental scenario and corresponding ERC	<u>Treatment of plastics:</u> ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)
---	---

Contributing Scenarios	<u>Treatment of plastics:</u> PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Treatment of plastics



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		64/96
Last revised date :	11.04.2022		

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used

Daily amount per site	76 tonnes
Regional use tonnage:	1073 tonnes/day

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		65/96
Last revised date :	11.04.2022		

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

SDS_SE - 000010021772



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		66/96
Last revised date :	11.04.2022		

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded. Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Treatment of plastics

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		67/96
Last revised date :	11.04.2022		

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1, PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor use				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions, Transfer of substance or mixture (charging and discharging) at dedicated facilities

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		68/96
Last revised date :	11.04.2022		

Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Handle product within a closed system.				Transfer of substance or mixture (charging and discharging) at dedicated facilities
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		69/96
Last revised date :	11.04.2022		

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable gloves tested to EN374: 90 %			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable face shield.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable coveralls to prevent exposure to the skin.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
		Use suitable eye protection.		Transfer of substance or mixture (charging and discharging) at dedicated facilities

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		70/96
Last revised date :	11.04.2022		

Environment:

Treatment of plastics:

none

Health:

Treatment of plastics:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 7.

Exposure scenario worker

1. Industrial use, Non-metal-surface treatment products, Treatment of textiles

List of use descriptors	
Sector(s) of use	SU5: Manufacture of textiles, leather, fur
Product categories [PC]:	PC34: Textile dyes and impregnating products

Name of contributing environmental scenario and corresponding ERC	<u>Treatment of textiles:</u> ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)
---	---

Contributing Scenarios	<u>Treatment of textiles:</u> PROC4: Chemical production where opportunity for exposure arises PROC6: Calendering operations
------------------------	--



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		71/96
Last revised date :	11.04.2022		

2.1. Contributing exposure scenario controlling environmental exposure for: Treatment of textiles

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used

Daily amount per site	76 tonnes
Regional use tonnage:	1073 tonnes/day

Frequency and duration of use

Batch process:	330 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		72/96
Last revised date :	11.04.2022		

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		73/96
Last revised date :	11.04.2022		

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Treatment of textiles

Process Categories:	PROC4: Chemical production where opportunity for exposure arises PROC6: Calendering operations
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		74/96
Last revised date :	11.04.2022		

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC4
No data available.			PROC6

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor use				Chemical production where opportunity for exposure arises
No data available.				Calendering operations

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Chemical production where opportunity for exposure arises
During indoor processes or in cases where natural ventilation is not				Chemical production where opportunity for exposure arises



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		75/96
Last revised date :	11.04.2022		

sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				
No data available.				Calendering operations

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Chemical production where opportunity for exposure arises



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		76/96
Last revised date :	11.04.2022		

	Wear suitable gloves tested to EN374: 90 %			Chemical production where opportunity for exposure arises
	Wear suitable face shield.			Chemical production where opportunity for exposure arises
	Wear suitable coveralls to prevent exposure to the skin.			Chemical production where opportunity for exposure arises
		Use suitable eye protection.		Chemical production where opportunity for exposure arises
No data available.	No data available.	No data available.		Calendering operations

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Treatment of textiles:

none

Health:

Treatment of textiles:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 8.

SDS_SE - 000010021772



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		77/96
Last revised date :	11.04.2022		

Exposure scenario worker

1. Professional use, Laboratory activities

List of use descriptors	
Sector(s) of use	SU24: Scientific research and development
Product categories [PC]:	PC21: Laboratory chemicals

Name of contributing environmental scenario and corresponding ERC	<u>Using gas alone or in mixtures for the calibration of analysis equipment:</u> ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)
---	--

Contributing Scenarios	<u>Using gas alone or in mixtures for the calibration of analysis equipment:</u> PROC15: Use as laboratory reagent
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		78/96
Last revised date :	11.04.2022		

Annual amount per site	No data available.
Regional use tonnage (tons/year):	No data available.

Frequency and duration of use

Batch process:	not relevant
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		79/96
Last revised date :	11.04.2022		

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas alone or in mixtures



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		80/96
Last revised date :	11.04.2022		

for the calibration of analysis equipment.

Process Categories:	PROC15: Use as laboratory reagent
---------------------	-----------------------------------

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	< 8 h	5 days per week	PROC15

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor use				Use as laboratory reagent

Other relevant operational conditions:	. See section 8 of the SDS.
--	-----------------------------



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		81/96
Last revised date :	11.04.2022		

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Use as laboratory reagent
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Use as laboratory reagent
Local exhaust ventilation				Use as laboratory reagent

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		82/96
Last revised date :	11.04.2022		

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Use as laboratory reagent
	Wear suitable gloves tested to EN374: 90 %			Use as laboratory reagent
	Wear suitable face shield.			Use as laboratory reagent
	Wear suitable coveralls to prevent exposure to the skin.			Use as laboratory reagent
		Use suitable eye protection.		Use as laboratory reagent

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:
Using gas alone or in mixtures for the calibration of analysis equipment.:



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		83/96
Last revised date :	11.04.2022		

none

Health:

Using gas alone or in mixtures for the calibration of analysis equipment.:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 9.

Exposure scenario worker

1. Professional use, Refilling of refrigeration equipment

List of use descriptors	
Sector(s) of use	
Product categories [PC]:	PC16: Heat transfer fluids

Name of contributing environmental scenario and corresponding ERC	<u>Refilling of refrigeration equipment:</u> ERC9a: Widespread use of functional fluid (indoor) ERC9b: Widespread use of functional fluid (outdoor)
---	---

Contributing Scenarios	<u>Refilling of refrigeration equipment:</u> PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Refilling of refrigeration equipment



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		84/96
Last revised date :	11.04.2022		

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used

Annual amount per site	No data available.
Regional use tonnage (tons/year):	No data available.

Frequency and duration of use

Batch process:	not relevant
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		85/96
Last revised date :	11.04.2022		

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		86/96
Last revised date :	11.04.2022		

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded. Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Refilling of refrigeration equipment

Process Categories:	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		87/96
Last revised date :	11.04.2022		

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC22

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor use				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		88/96
Last revised date :	11.04.2022		

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
	Wear suitable gloves tested to EN374: 90 %			Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
	Wear suitable face shield.			Transfer of substance or mixture (charging and discharging) at non-dedicated facilities



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		89/96
Last revised date :	11.04.2022		

	Wear suitable coveralls to prevent exposure to the skin.			Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
		Use suitable eye protection.		Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Refilling of refrigeration equipment:

none

Health:

Refilling of refrigeration equipment:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 10.

Exposure scenario worker

1. Professional use, Water treatment chemicals

List of use descriptors

SDS_SE - 000010021772



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		90/96
Last revised date :	11.04.2022		

Sector(s) of use	SU23: Electricity, steam, gas water supply and sewage treatment
Product categories [PC]:	PC37: Water treatment chemicals

Name of contributing environmental scenario and corresponding ERC	<u>Water treatment.:</u> ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)
---	--

Contributing Scenarios	<u>Water treatment.:</u> PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Water treatment.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,7 mPa.s (120,0 °F/48,9 °C)

Amounts used

Annual amount per site	No data available.
Regional use tonnage (tons/year):	No data available.

Frequency and duration of use

Batch process:	not relevant
Continuous process:	not relevant



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		91/96
Last revised date :	11.04.2022		

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m ³ /d	10	10	not relevant	

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		92/96
Last revised date :	11.04.2022		

Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Water treatment.

Process Categories:	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	---

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		93/96
Last revised date :	11.04.2022		

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	8574 hPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor use				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		94/96
Last revised date :	11.04.2022		

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Transfer of substance or mixture (charging and discharging) at dedicated facilities
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation	dermal exposure	eye exposure	oral exposure	Remarks
------------	-----------------	--------------	---------------	---------



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		95/96
Last revised date :	11.04.2022		

exposure				
				See chapter 8 of the safety data sheet (Personal protection equipment)
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.: 95 %				Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable gloves tested to EN374: 90 %			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable face shield.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
	Wear suitable coveralls to prevent exposure to the skin.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
		Use suitable eye protection.		Transfer of substance or mixture (charging and discharging) at dedicated facilities

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

SDS_SE - 000010021772



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ammonia, anhydrous

Issue Date:	16.01.2013	Version: 2.3	SDS No.: 000010021772
Revision Date:	05.04.2024		96/96
Last revised date :	11.04.2022		

Water treatment.:

none

Health:

Water treatment.:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>